



Date:

No:

Attachment:

Apafeed petrochemical trading LLC

DRILLING FLUIDS PRODUCT DATA

PAC L.V

Product Description:

PAC L.V is a low viscosity poly anionic cellulose, provides filtration control without significantly increasing viscosity. It could be used in fresh water to salt saturated waters.

Application:

- Fluid loss control.
- Wall – cake stabilization.
- Hole cleaning.

Typical Physical Properties:

MUD COMPOSITION					
COMPOSITION		1	2	3	4
S.S.W	ML	350	350	350	350
PAC L.V	GR	8	8	8	8
LIMESTONE (P)	GR	-	113	-	-
BARITE	GR	-	-	228	830
FER-O-BAR	GR	-	-	-	45
LIME SOLUTION	DROP	Few	Few	Few	Few
DENSITY	PCF	75	85	100	145

TEST RESULTS AFTER ROLLING AT 300 °F FOR 4 HRS. READING RHEOLOGY AT 140 °F					
RESULTS		REQ	REQ	REQ	REQ
APP. VIS	CPS	15	20	25	85
Y.P	LBS/100FT ²	2+	2+	2+	18+
GEL S. 10 Sec/10 min	LBS/100FT ²	1/2	1/2	1+/2+	2+/3+
pH		7-9.5	7-9.5	7-9.5	7-9.5
API. W.L	ML	<15	<10	<5	<5
SETTELLING		NIL	NIL	NIL	NIL

PAC L.V Continue:

Recommended Treatment:

0.5 – 5 lb/bbl.

Source:

KPA

Packaging:

25 Kg Kraft bags with PE liner, palletized and shrink - wrapped.
Marked on: Name of manufacturer, Batch No. and Production date.

Safety Handling:

- Non – toxic.
- Keep in dry and sheltered place.

